

Product Description

Product Name: Huawei 10000mAh Super Charge Power Bank AP09S

Dimension(L*W*H) with package: 163*108*19.5 mm

Weight with package: 316 g

Color: Black

1. Product Detail

- (1) Huawei patented SuperCharge Technology, and support max. 22.5W bidirectional super fast charging;
- (2) Input: 5V4.5A, 9V2A, 5V2A or 5V1A; Output: 5V4.5A, 9V2A, 5V2A or 5V1A;
- (3) Type C input and output, 40cm Type-C Data Cable incl.;
- (4) High-density lithium polymer cell with 12-layer safety features;
- (5) Smart LED indicator lights which show the remaining volume and the fast charging status(green light indication);
- (6) Stylish aluminum body with good feeling;
- (7) Cell Capacity: 2x5000mAh/37Wh;
- (8) Passed Tüv Rheinland CB Test and have Tüv Rheinland AK certificate;
- (9) CE certificated, strictly follow safety rules, top quality to use;

2. Product View



3. Hardware Parameters

Item	Description
Shape	Rectangular block
Dimensions	138 mm X 71 mm X 16 mm
Weight	About 252 g
Input port	Type-C
Input voltage	5V/9V
Input current	5V/9V:2A(MAX),5V/4.5A(MAX)
Output port	USB-A
Output voltage	5V/9V
Output current	5V/9V:2A,4.5V:5A,5V:4.5A
Output ripple	Non-SCP mode: Less than 150 mV at 5 V and 200 mV at 9 V SCP mode: Less than 80 mV
Output conversion	Greater than 91% at 5V& 9V (device only, without cable)

Item	Description
efficiency	
Device power consumption	Less than 150 uA
Battery cells	Polymer 606588 cells
Power level notifications	3 white LEDs + 1 two-color LED (Green when fast charging and white when not fast charging)
Button type	Buttons which only require a light touch
Charge loop counts	After 300 times, the remaining level of the battery will not be less than 80% of the rated capacity
Operating temperature	- Charging temperature: 0°C–40°C - Discharging temperature: -10°C to +45°C
Storage temperature	- Relative humidity less than 85% PH - Do not store at 45°C–55°C - Can store for three months at -20°C to +45°C - Can store for six months at -20°C to +35°C
Certifications	Version for China: MSDS,ROHS,REACH International version: ROHS,REACH,MSDS ,CB,CE,KC,UN38.3, 1.2 m drop test

4. Software Parameters

Item	Indicator light	Status Description
Remaining power indicator	●●●●	Each time you press the button, the indicator lights will illuminate for 6 seconds and then turn off. ◎ means flashing; ● means on; ○ means off
	○○○○	The remaining battery power is less than 5%. It needs to be recharged.
	●○○○	5%–25% remaining battery power
	●●○○	25%–50% remaining battery power
	●●●○	50%–75% remaining battery power
	●●●●	75%–100% remaining battery power
Charging indicator	◎○○○	The battery has been charged 25%
	●◎○○	The battery has been charged 25%–50%
	●●◎○	The battery has been charged 50%–75%
	●●●◎	The batter has been charged 75%–100%
	●●●●	The battery is fully charged

Obsah je uzamčen

**Dokončete, prosím, proces objednávky.
Následně budete mít přístup k celému dokumentu.**



Proč je dokument uzamčen? Nahněvat Vás rozhodně nechceme. Jsou k tomu dva hlavní důvody:

- 1) Vytvořit a udržovat obsáhlou databázi návodů stojí nejen spoustu úsilí a času, ale i finanční prostředky. Dělali byste to Vy zadarmo? Ne*. Zakoupením této služby obdržíte úplný návod a podpoříte provoz a rozvoj našich stránek. Třeba se Vám to bude ještě někdy hodit.

**) Možná zpočátku ano. Ale vězte, že dotovat to dlouhodobě nelze. A rozhodně na tom nezbohatneme.*

- 2) Pak jsou tady „roboti“, kteří se přiživují na naší práci a „vysávají“ výsledky našeho úsilí pro svůj prospěch. Tímto krokem se jim to snažíme překazit.

A pokud nemáte zájem, respektujeme to. Urgujte svého prodejce. A když neuspějete, rádi Vás uvidíme!